


BOP HOSE

BOP Armor



Better Against Abrasion

Popular with our API crimp fitting for its larger hex and longer threads for easier installation of hammer unions.

Approvals

(both require the hose to handle 1,300° F for 5 minutes)

API 16D Control Systems for Drilling Well Control Equipment

Lloyd's Register's Fire Tests for Flexible Hoses on Offshore Installations, OD 1000/499

Tube Synthetic rubber

Cover Stainless steel armor, .08" armor wall, protects against impacts, wear, handling, etc.


Reinforcement High tensile steel wire spiral layers

Fire Protection 1500° F rated thermal blanket, non-flammable, non-conductive



Fire Rating Can handle flame temperature 1,300° F for 5 minutes (API 16D requirements)

BOP Red



More Flexible, Lighter Weight

Popular with our API crimp fitting for its larger hex and longer threads for easier installation of hammer unions.

Approvals

(both require the hose to handle 1,300° F for 5 minutes)

API 16D Control Systems for Drilling Well Control Equipment

Lloyd's Register's Fire Tests for Flexible Hoses on Offshore Installations, OD 1000/499

Tube Synthetic rubber

Cover Fire resistant synthetic rubber impregnated with fiberglass

Reinforcement High tensile steel wire spiral layers



Fire Rating Can handle flame temperature 1,300° F for 5 minutes (API 16D requirements)