

# Level Indication > Systems **Level Switches**

**There is an array of single-point level indication products ideal for level alarms, emergency shut downs, pump start / stop and any other application that requires activation based on tank fluid level.**

## Electric Gauge Board Switches

The EXA-AR is a gauge board-mounted electrical switch, activated by the traversing indicator. Mounted externally, the gauge board switch not only offers simple set-point adjustment and easy maintenance and installation, but also requires no additional tank nozzle connection. The EXA-AR can be installed before or after gauge board installation, and come standard with a whisker trigger.



**Above:** EX-AR Switch with Board Mounting  
**Below:** Pneumatic switch with magnetic mounting

## Pneumatic Gauge Board Indicator Switches

The pneumatic switch is a 2-position 3-way device. It comes standard with magnetic mounting bracket and whisker trigger. The magnetic bracket offers flexibility in mounting and simple set-point adjustment, while the long whisker ensures the indicator fully throws the switch.



## Specifications

Switch	EX-AR	Pneumatic
Act. Princip.	Snap Action Whisker Lever	Whisker Lever
Operation	Mechanical / Electrical	Pneumatic
HazLoc	CSA Cl. I Div I Gr. B,C,D	—
Output	SPDT	2-Pos 3-way
Power	600 VAC Max	—
Process Connection	Gauge Board (3/4 NPT Conduit)	Gauge Board
Temperature	-40° C to 121 °C	—
Pressure	—	250 psi