

S E R I E S M D K

SEALER DISC

20-48" (508-1219mm)

Size	O.D	I.D	Thick	# Holes	Hole Dia	Bolt Circle	Weight	Part #
20"	20.00	10.87	0.75	12	0.812	13.50	7.92	91-7200-20
24"	24.00	14.18	1.00	12	0.812	16.93	14.18	91-7200-24
30"	30.00	18.15	1.00	12	0.875	22.00	21.57	91-7200-30
36"	36.00	22.25	1.25	12	0.875	25.27	37.86	91-7200-36
42"	43.12	26.25	1.25	12	0.937	29.05	55.32	91-7200-42
48"	49.00	28.25	1.25	12	0.937	31.89	71.19	91-7200-48

GUIDE DISC

20-48" (508-1219mm)

Size	O.D	I.D	Thick	# Holes	Hole Dia	Bolt Circle	Weight	Part #
20"	19.25	10.87	1.25	12	0.812	13.50	8.84	91-7205-20
24"	23.25	14.18	1.50	12	0.812	16.93	19.26	91-7205-24
30"	29.30	18.15	1.50	12	0.875	22.00	30.00	91-7205-30
36"	35.00	22.25	1.75	12	0.875	25.27	48.31	91-7205-36
42"	40.75	26.25	2.25	12	0.937	29.05	82.66	91-7205-42
48"	46.63	28.25	2.37	12	0.937	31.89	123.35	91-7205-48

MDK-ED pigs are equipped with durable guide discs, one at each end. The guide discs provide a positive centering affect which allow the four sealing discs in the center to effectively seal during the displacement period.

All Apache discs are manufactured from high quality polyurethane and are available with a variety of wear resistant additives. Apache has also developed a proprietary chemically-resistant urethane suited specifically for severe environments such as hydrogen sulphide gas.